



R-T表

广东爱晟电子科技有限公司

R25(KΩ)	10	阻值精度	1.0%	型号: DT103F3435B			
B25/85	3435	B值精度	1.0%				
Temp(°C)	Rmin(KΩ)	Rnor(KΩ)	Rmax(KΩ)	Temp(°C)	Rmin(KΩ)	Rnor(KΩ)	Rmax(KΩ)
-40	197.185	205.288	213.702	3	23.7674	24.2208	24.6804
-39	186.304	193.849	201.678	4	22.7802	23.2048	23.6350
-38	176.099	183.126	190.414	5	21.8399	22.2375	22.6401
-37	166.522	173.069	179.855	6	20.9438	21.3161	21.6928
-36	157.532	163.633	169.954	7	20.0898	20.4383	20.7908
-35	149.088	154.776	160.665	8	19.2756	19.6018	19.9315
-34	141.154	146.458	151.947	9	18.4991	18.8044	19.1127
-33	133.695	138.643	143.760	10	17.7584	18.0440	18.3323
-32	126.680	131.297	136.069	11	17.0516	17.3187	17.5882
-31	120.080	124.390	128.841	12	16.3770	16.6268	16.8786
-30	113.868	117.891	122.044	13	15.7330	15.9664	16.2017
-29	108.018	111.775	115.651	14	15.1179	15.3361	15.5558
-28	102.507	106.017	109.635	15	14.5304	14.7342	14.9393
-27	97.314	100.592	103.971	16	13.9690	14.1593	14.3507
-26	92.417	95.481	98.636	17	13.4325	13.6101	13.7886
-25	87.799	90.662	93.610	18	12.9196	13.0852	13.2517
-24	83.441	86.118	88.872	19	12.4291	12.5836	12.7386
-23	79.327	81.831	84.405	20	11.9600	12.1039	12.2483
-22	75.443	77.784	80.190	21	11.5112	11.6452	11.7796
-21	71.773	73.964	76.213	22	11.0817	11.2064	11.3313
-20	68.306	70.355	72.458	23	10.6706	10.7865	10.9026
-19	65.014	66.931	68.898	24	10.2770	10.3847	10.4925
-18	61.903	63.697	65.536	25	9.9000	10.0000	10.1000
-17	58.960	60.639	62.359	26	9.5318	9.6317	9.7316
-16	56.176	57.747	59.357	27	9.1792	9.2789	9.3787
-15	53.542	55.012	56.518	28	8.8416	8.9409	9.0404
-14	51.047	52.424	53.833	29	8.5182	8.6171	8.7162
-13	48.685	49.974	51.292	30	8.2084	8.3067	8.4053
-12	46.446	47.654	48.888	31	7.9114	8.0091	8.1072
-11	44.325	45.456	46.611	32	7.6268	7.7238	7.8212
-10	42.314	43.373	44.454	33	7.3540	7.4501	7.5468
-9	40.407	41.399	42.411	34	7.0923	7.1876	7.2835
-8	38.597	39.526	40.474	35	6.8413	6.9357	7.0308
-7	36.879	37.750	38.637	36	6.6005	6.6940	6.7881
-6	35.249	36.065	36.896	37	6.3694	6.4619	6.5551
-5	33.701	34.465	35.243	38	6.1476	6.2391	6.3313
-4	32.229	32.946	33.674	39	5.9347	6.0251	6.1162
-3	30.832	31.502	32.185	40	5.7302	5.8195	5.9096
-2	29.503	30.131	30.770	41	5.5339	5.6220	5.7111
-1	28.239	28.828	29.426	42	5.3452	5.4323	5.5202
0	27.037	27.589	28.149	43	5.1640	5.2498	5.3366
1	25.893	26.410	26.934	44	4.9898	5.0745	5.1601
2	24.804	25.288	25.779	45	4.8223	4.9059	4.9903



R-T表

广东爱晟电子科技有限公司

R25(KΩ)	10	阻值精度	1.0%	型号: DT103F3435B			
B25/85	3435	B值精度	1.0%				
Temp(°C)	Rmin(KΩ)	Rnor(KΩ)	Rmax(KΩ)	Temp(°C)	Rmin(KΩ)	Rnor(KΩ)	Rmax(KΩ)
46	4.6613	4.7437	4.8270	89	1.2600	1.2990	1.3390
47	4.5065	4.5877	4.6698	90	1.2255	1.2638	1.3031
48	4.3576	4.4376	4.5185	91	1.1922	1.2297	1.2683
49	4.2144	4.2931	4.3729	92	1.1598	1.1967	1.2346
50	4.0766	4.1541	4.2327	93	1.1285	1.1647	1.2019
51	3.9443	4.0206	4.0980	94	1.0981	1.1336	1.1702
52	3.8169	3.8920	3.9682	95	1.0687	1.1036	1.1394
53	3.6943	3.7682	3.8432	96	1.0402	1.0744	1.1096
54	3.5763	3.6490	3.7228	97	1.0125	1.0461	1.0807
55	3.4626	3.5342	3.6068	98	0.9857	1.0187	1.0526
56	3.3531	3.4235	3.4950	99	0.9597	0.9921	1.0254
57	3.2476	3.3168	3.3872	100	0.9345	0.9662	0.9990
58	3.1460	3.2140	3.2832	101	0.9100	0.9412	0.9733
59	3.0480	3.1149	3.1830	102	0.8863	0.9169	0.9484
60	2.9536	3.0194	3.0863	103	0.8633	0.8933	0.9243
61	2.8626	2.9272	2.9930	104	0.8409	0.8704	0.9008
62	2.7748	2.8383	2.9030	105	0.8192	0.8482	0.8781
63	2.6901	2.7526	2.8162	106	0.7982	0.8266	0.8560
64	2.6084	2.6698	2.7324	107	0.7778	0.8057	0.8345
65	2.5297	2.5900	2.6514	108	0.7580	0.7853	0.8136
66	2.4536	2.5129	2.5733	109	0.7387	0.7656	0.7934
67	2.3802	2.4384	2.4978	110	0.7200	0.7464	0.7737
68	2.3094	2.3666	2.4249	111	0.7019	0.7278	0.7546
69	2.2410	2.2972	2.3545	112	0.6842	0.7097	0.7360
70	2.1750	2.2301	2.2865	113	0.6671	0.6921	0.7179
71	2.1112	2.1654	2.2208	114	0.6505	0.6750	0.7004
72	2.0496	2.1028	2.1572	115	0.6343	0.6584	0.6833
73	1.9901	2.0423	2.0958	116	0.6186	0.6423	0.6668
74	1.9325	1.9839	2.0364	117	0.6034	0.6266	0.6506
75	1.8770	1.9274	1.9790	118	0.5886	0.6113	0.6350
76	1.8232	1.8728	1.9234	119	0.5741	0.5965	0.6197
77	1.7713	1.8199	1.8697	120	0.5601	0.5821	0.6049
78	1.7211	1.7688	1.8177	121	0.5465	0.5681	0.5905
79	1.6725	1.7194	1.7675	122	0.5333	0.5545	0.5765
80	1.6256	1.6716	1.7188	123	0.5204	0.5412	0.5628
81	1.5794	1.6246	1.6710	124	0.5079	0.5283	0.5495
82	1.5348	1.5792	1.6247	125	0.4957	0.5158	0.5366
83	1.4916	1.5352	1.5799	126	0.4839	0.5036	0.5241
84	1.4498	1.4926	1.5365	127	0.4724	0.4917	0.5118
85	1.4094	1.4513	1.4944	128	0.4612	0.4802	0.4999
86	1.3702	1.4114	1.4537	129	0.4503	0.4690	0.4884
87	1.3323	1.3727	1.4143	130	0.4397	0.4580	0.4771
88	1.2956	1.3353	1.3760	131	0.4293	0.4474	0.4661

